

Required duty point			
Volume flow	1800 m ³ /h	Pressure	20 Pa st.
Density	1,22 kg/m ³	Temperature	15 °C

Technical details			
Art.No. / Type	104695 / RV 250-E EC ErP2018		
Volume flow	1800 m ³ /h	Fan speed	3382 min ⁻¹
Total pressure	57 Pa	Efficiency	11 %
Static pressure	20 Pa	Sound power	83 dB(A)
Absorbed power	0,26 kW	Nominal power	0,31 kW
Voltage	1/PE AC 230 V	Frequency	50/60 Hz
Rated current I _N	1,37 A	Weight/pc. appr.	12,5 kg

ErP 1253 data			
Wolter GmbH		RV 250-E EC ErP2018	
Type	NRVU, UVU		
Drive	variable speed (integrated)		
Heat recovery system	none	Flow rate q _{nom}	0,2461 m ³ /s
Input P _e	0,31 kW	SFP _{int}	n/a Ws/m ³
Face velocity	3,9 m/s	Nom. ext. pressure Δp _{s,ext}	626 Pa
Overall efficiency η _e	49,8 %	Sound power level L _{WA}	79 dB
ErP 1253	2018		
--	--		

Octave frequency sound								
f _M [Hz]	LWA	125	250	500	1k	2k	4k	8k
LWA5 [dB(A)]	80	55	68	73	74	74	73	65
LWA8 [dB(A)]	83	57	68	75	78	78	75	65

