

Required duty point			
Volume flow	7000 m ³ /h	Pressure	20 Pa st.
Density	1,22 kg/m ³	Temperature	15 °C

Technical details			
Art.No. / Type	104750 / RV 450-D EC ErP2018		
Volume flow	7000 m ³ /h	Fan speed	1733 min ⁻¹
Total pressure	47 Pa	Efficiency	9 %
Static pressure	20 Pa	Sound power	85 dB(A)
Absorbed power	0,99 kW	Nominal power	1,6 kW
Voltage	3/PE AC 400 V	Frequency	50/60 Hz
Rated current I _N	2,6 A	Weight/pc. appr.	37,0 kg

ErP 1253 data			
Wolter GmbH		RV 450-D EC ErP2018	
Type	NRVU, UVU		
Drive	variable speed (integrated)		
Heat recovery system	none	Flow rate q _{nom}	1,2844 m ³ /s
Input P _e	1,59 kW	SFP _{int}	n/a Ws/m ³
Face velocity	4,4 m/s	Nom. ext. pressure Δp _{s,ext}	655 Pa
Overall efficiency η _e	54,0 %	Sound power level L _{WA}	81 dB
ErP 1253	2018		
--	--		

Octave frequency sound								
f _M [Hz]	LWA	125	250	500	1k	2k	4k	8k
LWA5 [dB(A)]	80	63	73	74	74	73	68	61
LWA8 [dB(A)]	85	66	78	80	80	76	70	62

RV 450-D EC ErP2018

